



MC = Maximum Clearance

CP/BE = Center of Post to Back Edge of tail section

CA = Cab to Axle

CT = Cab to Trunion (center of tandem axle)

Ultimate:

TRUCKBED LENGTH	20'	22'	24'	26'	28'	30'
CONVEYOR LENGTHS	30' 32'	34'	36'	38'	40'	40'
CAB TO AXLE (CA) / CAB TO TRUNION (CT)						
<i>MINIMUM</i>	110"	132"	157"	179"	206"	230"
<i>RECOMMENDED</i>	116"	140"	165"	187"	214"	240"
<i>MAXIMUM</i>	128"	152"	177"	199"	226"	252"

Deluxe:

LENGTHS	24'	26'	28'	30'	32'
WEIGHTS	1700 lbs	1775 lbs	1850 lbs	1925 lbs	2000 lbs
CHAIN SPEED	**				
PADDLE SPACING	58"				
FRAME STRUCTURE	Stainless Steel				
SHINGLE DELIVERY SYSTEM	CA-550 Chain and Stainless Steel Paddle				
REMOTE CONTROLLED OPERATIONS	Not Available				
POST	Hydraulic Fixed Height Optional Hydraulic Telescoping Post Rotation 360°				
CAB TO AXLE (CA) CAB TO TURNION (CT)	See the CA / CT tab				
LOAD AND CLEARANCE	See the CA / CT tab				